

STS-System Benefits

- TÜV certificate according to the legal and standard requirements
- For safety applications up to PLe/Category 4 according to EN/ISO 13849-1
- Modular and expandable system
- Rugged stainless steel design
- Wireless mechanical safeguarding
- Combines the benefits of safety switch, solenoid locking and key transfer in a single system
- Easy installation through comprehensive accessories
- Protection against lock-in

Features STS-SXB01M

The unit is particularly suitable for applications with:

- Full body access (lock-in danger)
- Several secured entries
- Single-channel/ redundant/ diverse safety circuits
- Rugged ambient conditions

Approvals and marking



Function

Safety switch (type 2) for separating guards with optional key removal.

Application

To secure separating guards such as safety gates and hoods in machine and plant engineering.

Design and Operation

Attention!



Hazards must be ruled out before the movable part of the guard can be opened!
Optionally, a key can then be removed.

The STS switch unit must be integrated into a system and connected with a control unit so that the hazardous machine can only run when the guard is locked and closed.

The key can be removed at any time, whereby hazards must be ruled out immediately. If the access is opened and the actuator is removed from actuator module B the key can be removed from key module 01. The door is now blocked when open and an escape route is thus secured. Only after the key has been returned to its starting position and the door was then closed can the machine be restarted. Opening of the access is queried by the contacts of actuator monitoring.

STS-SXB01M is usually used in the system in connection with additional STS units and SAFEMASTER products (e.g. Emergency stop module LG 5925, Softstarter with DC-Brake BL 9228). The key with optional removal can serve as protection against lock-in or for the operating release of these units (e.g. STS-M10A, STS-M11A, STS-M12M, STS-M10B01M).




Fig. 1:
Locked while activated:
Actuator and key inserted,
Door closed




Fig. 2:
Lock deactivated:
Actuator removed
Door open

Switching logic

			Fig. 1	Fig. 2
Door contacts	3	2		
	3	1		
	9	11		
	9	10		
	7	8		

closed
 open

Enclosure: Stainless steel V4A / AISI 316L
 Degree of protection: IP 65
 Temperature range: - 25 °C to + 65 °C
 Storage temperature: - 40 °C to + 80 °C
 Mechanical principle: Rotating axis with redundant actuator
 Connection method: cage tension spring clamps
 min. connection cross-section: 0.25 mm²
 max. connection cross-section: 1.5 mm²
 Cable entry: 1 x M20 x 1,5
 B10_g: 2 x 10⁶ switching cycles
 Electrical service life: 5 x 10⁶ switching cycles
 min. operating speed: 100 mm/s
 max. operating speed: 500 mm/s
 (by exception, 1500 mm/s is permitted)
 max. switching frequency: 360/h
 Nominal voltage U_N: AC/DC 24 V
 Nominal voltage range: 0.85 ... 1.1 U_N
 Power consumption: 0.3 W
 Rated impulse voltage: 0.8 kV
 Rated insulation voltage: < 60 V
 Contacts: 1 NC contact, 2 diverse changeovers contacts
 Switching principle: Changeover contact with forced-opening snap-action switch
 max. operating current: 2 A
 Short circuit strength, max. fusing: 4A gG
 Contact material: Ag / AgSnO₂
 Indicator: LED red/green, separate selection possible
 Test principles: EN ISO 13849-1:2008
 EN 1088+A2:2008
 EN 60947-5-1:2005
 GS-ET 19:04.2004
 Intended use: up to max. cat. 4, PL e according to EN ISO 13849-1
 Mounting: according to DIN EN 50041
 Contact elements: IEC EN 60947-5-1 Appendix K
 Additional requirement for cat. 4 structure (as single unit): Add 2nd actuator module, Type STS-SXBB01M
 Diagnostic coverage (DC), (mechanical):
Logic and output
 STS-SXB01M
 STS-SXBB01M
 Fault exclusions: none
 Protection against faults of common cause: see table in STS design guide by manufacturer only
 Repair and replacement: semi-annually recommended
 Test intervals: min. once a year

cat. 2	cat. 3	cat. 4
84 %	85 %	85 %
98 %	99 %	99 %
none		

Variants and Combination Options

Because of their modular design the basic units of the Safemaster STS System can be combined and expanded according to customer requests. This allows for a variety of possible units and functions.

Overview of the basic units

Group of the basic unit	Application			
	Basic function with separate actuator	Forced key removal as protection against lock-in or to operate additional units	Optional key removal as protection against lock-in or to operate additional units	Units without actuator
Mechanical	STS-M10A	STS-M11A	STS-M10B01M	STS-M12M
Locking	STS-ZRHA	STS-ZRH01A	STS-ZRHB01M	STS-ZRH01M
Switch	STS-SXA	STS-SX01A	STS-SXB01M	STS-SX01M

For additional information refer to the data sheets of the individual modules and other basic units.


Data sheets

STS Solenoid locking modules SX/SV
 STS Actuator module B
 STS Key module 01/10
 STS End module M




Take advantage of the advice of the **E. DOLD & SÖHNE KG** specialists regarding the choice of units and combination of a system.

Ordering Example



Dimensional Drawing [mm]



Clearance tolerances $\pm 2\%$

